APPROVED

04/17

PENLUBE

PENLUBE is a high tech formulation of specific oils blended with micron-sized PTFE to provide exceptional long lasting lubrication and penetration. **PENLUBE** significantly decreases friction and distributes a wear-resistant film that lubricates moving parts. The initial foaming action allows for dwell time so it can creep into tight spaces. **PENLUBE** penetrates rapidly to loosen frozen parts due to rust, wear, or heavy grease build up. The lubricating film guards surfaces from corrosion in extreme hot and cold temperatures. Use **PENLUBE** on any surfaces that glides, slides, rolls, twists, or moves. Passes ASTM D 1748 - Rust protection by metal preservatives in the humidity cabinet.

DIRECTIONS FOR USE:

- 1. Shake well before using.
- 2. Spray liberally on frozen or corroded part.
- 3. Let stand for several minutes to allow thorough penetration.
- 4. Reapply for long-lasting protection.

PRECAUTIONARY STATEMENT: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Wash thoroughly after handling. Wear eye protection/face protection. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

CONTAINS (CAS No.): Mineral Oil, Petroleum Distillates, Solvent-Dewaxed Heavy Paraffinic (CAS#64742-65-0), Aromatic Hydrocarbon Mixture (CAS#64742-95-6), Mineral Seal Oil (CAS#64742-46-7), Mineral Spirits (CAS#64475-85-0), Carbon Dioxide (CAS#124-38-9), Ethyl Alcohol (CAS#64-17-5), Amyl Acetate (CAS#628-63-7), Diethylene Glycol Monobutyl Ether (CAS#112-34-5).

Not available for sale in California. Other locales may also prohibit its sale or use. Check local and state regulations.

READ SAFETY DATA SHEET BEFORE USING. KEEP OUT OF REACH OF CHILDREN.

Made in U.S.A.

VOC Content: 43.1%.

To Reorder Call 866-578-4240 Fax: 866-578-4241

Fax: 866-578-4241 **Part Number: 1035**

Mfg. for: Algonquin Products Company
29 Russells Mills Rd
Dartmouth, MA 02748

