

# TECHNICAL DATA SHEET

## HIGHLIGHTS

- Penetrates
- Lubricates
- Displaces moisture
- Prevents corrosion

## TYPICAL PROPERTIES

- Specific Gravity: **0.8**
- Propellant: **Hydrocarbon**
- Spray Characteristics: **Streamy spray**
- Appearance: **Clear amber liquid**
- Odor: **Characteristic**
- Net Weight: **18 ounces**

## SAFETY CAUTIONS

- Keep out of reach of children.
- Contents under pressure. Do not expose to heat or store at temperatures exceeding 120° F. Do not use near sparks or open flames. Do not puncture or incinerate container. Wrap empty container and put in trash collection.
- Refer to M.S.D.S. for additional safety information.

## HMIS RATINGS



## PENLUBE

**4 IN 1 SPRAY:  
Lubricates, Penetrates,  
Displaces Moisture,  
Prevents Corrosion**

Penetrating Oil frees rusted and corroded nuts, bolts, studs, set screws, aluminum and copper fittings. Penetrating Oil also lubricates and prevents corrosion on rusted and frozen parts. Can be used on most metal, wood and painted surfaces. Use Penetrating Oil in garages, factories, on farm machinery, marine and aeronautical equipment, in shops and homes.

### DIRECTIONS:

- Hold container upright 6 to 8 inches from surface to be sprayed.
- Spray area to be treated liberally and allow sufficient time for complete penetration.
- Repeat treatment on extremely corroded parts.
- Tapping or heating may be required in some severe instances..

**DANGER:** DANGER! Extremely flammable. Avoid breathing vapor. Harmful or fatal if swallowed. Use only with adequate ventilation.

To Reorder Call: 866-578-4240

Fax: 866-578-4241

Part Number: 1035

**ALGONQUIN PRODUCTS CO.**

1165 Allgood Road Suite 13 • Marietta, GA 30062