HIGHLIGHTS

- High flash point
- Very low odor
- Safe on plastics

TYPICAL PROPERTIES

• Specific Gravity: 0.78

 Dielectric Breakdown Voltage: 29,600 volts

● Flash Point: 143°F

Evaporation Rate: 0.06

• Residue on Drying: None

• KB Value: **33**

• Appearance: Clear colorless liquid

• Odor: Slight petroleum distillate

• USDA: K-2

SAFETY CAUTIONS

- Keep out of reach of children.
- CAUTION: COMBUSTIBLE MIXTURE.
- It is recommended that protective gloves and safety glasses be worn when using this product.
- Make sure there is adequate ventilation.
- Refer to M.S.D.S. for additional safety information.



HMIS RATINGS

Flammability





PARTS KLEE

Low Odor Solvent Degreaser

This product is excellent for removing most greases, oils, lubricants, etc. It has low odor and low inhalation toxicity for maximum work comfort and safety. Non-conductive, high flash point, leaves no residue. Safe on ferrous and non-ferrous metals, and on many types of plastics, such as polyethylene, polypropylene, PETE, PVC and electrical wiring. This product may be substituted for chlorinated solvents in applications below.

DIRECTIONS:

- Cold degreasing: May be used for immersion cleaning in non-agitated vats, circulation-type units, ultrasonic, air-agitated and pressure-spray units. Soak until clean. If desired, remove parts from vat and spray fresh product to flush away dissolved soils. Let product evaporate, or blow dry with air.
- Electrical contact cleaning: May be used to clean electrical and electronic parts and equipment. Safe on electrical wiring. Deenergize equipment first and blow dry with air before turning back on. Do not spray on hot surfaces. Do not use on operating equipment that may spark or that has an open flame.

To Reorder Call: 866-578-4240 Fax: 866-578-4241 Part Number: 1044

ALGONQUIN PRODUCTS CO. 1165 Allgood Road Suite 13 • Marietta, GA 30062