HIGHLIGHTS

- Low-acid bowl cleaner
- Thick, clinging to vertical surfaces
- Pleasant fragrance

TYPICAL PROPERTIES

- Specific Gravity: 1.055
- pH: 0.5
- Acidity: 9.6%
- Viscosity: 100 cps
- Appearance: Clear blue liquid
- Fragrance: Mint
- USDA: C-2

SAFETY CAUTIONS

• Keep out of reach of children.

Corrosive

• It is recommended that protective gloves and safety glasses be worn when using this product.

• Make sure there is adequate ventilation.

• Refer to M.S.D.S. for additional safety information.



LIMITED DISINFECTANT AGAINST GRAM-NEGATIVE BACTERIA • CLEANS • DEODORIZES • DISINFECTS

Removes lime, soap scum, hard water deposits, uric acid salts, and various discolorations from toilet bowls, urinals, shower stalls, ceramic tiles and sinks. Effective against Salmonella choleraesuis when used undiluted on precleaned hard non-porous environmental surfaces, according to the AOAC Use Dilution Method.

DIRECTIONS-

To Clean Toilets and Urinals: Remove water by forcing it over the trap with swab mop. Saturate swab with this product and wet all surfaces thoroughly. It is most important to swab under the rim of bowl or urinal to clean water outlets. Allow this product to remain for at least 10 minutes until all rust, scale, and stains are loosened. Rinse by flushing.

To Clean Sinks, Bathtubs, Shower Stalls, Drinking Fountains, Ceramic Tile Floors: Dilute one part of this product with two parts water and apply to wet all surfaces thoroughly with swab mop, sponge, brush or cloth. Allow to remain for at least 10 minutes. Rinse with water after cleaning.

TO DISINFECT SURFACES LISTED ABOVE:
1. Before disinfecting, pre-clean the surfaces according to cleaning directions above.
2. Apply this product with swab mop, sponge, brush or cloth. Thoroughly wet all surfaces for a minimum contact time of 10 minutes.
3. Rinse thoroughly with potable water.

HMIS RATINGS



Manufactured For: ALGONQUIN PRODUCTS CO. 1165 Allgood Road Suite 13 • Marietta, GA 30062 To Reorder Call: 866-578-4240 Fax: 866-578-4241 Part Number: 1024 ALG-435 1024/605 rev.