

# TECHNICAL DATA SHEET

## HIGHLIGHTS

- Fast-acting
- Easy to use
- Removes oil and gasoline stains


## TYPICAL PROPERTIES

- pH (0.5% solution): **11.5**
- Alkalinity (as Na<sub>2</sub>O)  
Total: **26%**  
Active: **20%**
- Appearance: **Light orange (turns green on contact with water)**
- Odor: **Butyl**
- USDA: **C-1**

## SAFETY CAUTIONS

- Keep out of reach of children.
- It is recommended that protective gloves and safety glasses be worn when using this product.
- Refer to M.S.D.S. for additional safety information.

## HMIS RATINGS



## HD POWDERED FLOOR SOAP

### white side wall tire cleaner

A highly concentrated blend of detergents, alkali builders, emulsifiers and solvents for fast and effective removal of dirt and grease. IDEAL for use in garages, filling stations, bus terminals and other industrial areas.

### DIRECTIONS:

- **CONCRETE FLOORS:** Wet floors, sprinkle on and allow to set for a few minutes. Scour with deck brush and rinse with clean water. This product penetrates and emulsifies hard to get soils.
- **PRESSURE TYPE SPRAY SYSTEMS:** Add 3 to 5 pounds per 100 gallons of water in solution tank depending on pressure. High pressure units require less concentration than low pressure units.
- **MANUAL TIRE CLEANING:** Add 2 to 4 oz. per gallon of water. Apply with brush in circular motions. Rinse washed areas with plenty of clear water.

To Reorder Call: 866-578-4240  
Fax: 866-578-4241  
Part Number: 1023

**ALGONQUIN PRODUCTS CO.**  
1165 Allgood Road Suite 13 • Marietta, GA 30062